

## Combo DB-15 Two Console KVM



### Combo DB-15 Two Console KVM Benefits

- ▶ Combo DB-15 KVM with either 8 or 16 ports in 1U
- ▶ Remote access up to 300 meters
- ▶ Cascade switches up to 8 levels & Mix switches between Cat6 & Combo DB-15 KVM
- ▶ Mix PS/2, USB & SUN with Multi-Platform switch capability
- ▶ Cost efficient remote server management between user & equipment rooms within the building

### Switch Features & Options

- Multi lingual on screen display menu
- Advanced user profiles and configurable OSD hot key combinations
- Dual power with failover

**DC** 12V, 24V and 48V DC Power options



### Technical Specification

- **KVM Port :** 16 / 8 x DB-15 connector
- **KVM Cable :** Combo 4-in-1 KVM cable, up to 6, 10 & 15 feet
- **Console**  
Local : 1 x DB-15 VGA (up to 1600 x 1200), 2 x USB for KB & MS  
Remote : 1 x RJ45, up to 300 meters (1000 feet) Cat6 / Cat5 cable
- **Remote Receiver :**  
1 x VGA port (up to 1600 x 1200), 2 x USB for KB & MS  
1 x KVM port for connecting an extra PC
- **Expansion :** Support mixed Combo Cat6 or Combo DB-15 KVM, up to 240 servers
- **Compatibility :** Mix PCs, SUNs, MACs, IBMs, HPs, DELLs server  
Windows Vista / 2003 / XP / 2000, Linux, Netware, Unix
- **Power :** 100~240VAC, 50 / 60Hz 0.3A via IEC type cord (12V / 24V / 48V DC input option)
- **Regulatory Approval :** FCC, CE
- **Environmental**  
Operating / Storage : 0 to 50°C / -5 to 60°C  
Relative humidity : 90%, non-condensing  
Shock : 50G peak acceleration (11 ms, half-sine wave)  
Vibration : 58~100Hz / 0.98G (11ms / cycle)

### Accessories



Combo 4-in-1 KVM cable - 6, 10 & 15 ft



6ft Combo KVM cascade cable

### Dimensions

Model	Product Dimension (W x D x H)	Packing Dimension (W x D x H)	Net Weight	Gross Weight
-802 -1602	446 x 180 x 44 mm 17.6 x 7.1 x 1.73 inch	510 x 400 x 77 mm 20.1 x 15.7 x 3 inch	4 kg / 9 lbs	4.5 kg / 10 lbs