



Benefits

- ▶ 1U 17" / 19" LCD console drawer
- ▶ Dual slide - LCD and keyboard slide independently
- ▶ 1280 x 1024 native resolution / 16.7M colors
- ▶ 104-key keyboard with touchpad
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front handle and two point lock
- ▶ 2-year standard warranty (upgradable up to 5 years)

Options

- DVI-D / HDMI 1.2 video input
- S-Video + Composite (BNC)
- Audio input & output
- DC power : 12V / 24V / 48V / 125V
- MAC or SUN Micro keyboard options available

Product Specifications

| Console Port | |
|------------------------------|----------------------------------------------------------------------------|
| Video input | VGA |
| KB / MS | USB Interface |
| VGA console 6ft cable : CB-6 | Drawer end : DB-15 + USB type A x 2 Server end : DB-15 + USB type A x 2 |

| Video Option | | |
|--------------|-------------------|---------------------|
| Digital | DVI | DVI-D single link |
| | HDMI | HDMI 1.2 / HDCP 1.1 |
| Analog | S-Video (4-pin) | NTSC & PAL |
| | Composite (BNC) | NTSC & PAL |

| LCD Panel | RM-113-17 | RM-113-19 |
|----------------------------------|------------------------|-------------------|
| Panel size (diagonal) | 17" | 19" |
| Native resolution | 1280 x 1024 | 1280 x 1024 |
| Brightness (cd/m ²) | 250 | 250 |
| Contrast ratio (typ.) | 1000 : 1 | 1000 : 1 |
| Colors | 16.7 M | 16.7 M |
| Viewing angle (L/R/U/D) | 85/85/80/80 | 85/85/80/80 |
| Response time (ms) | 5 | 5 |
| Dot pitch (mm) | 0.264 | 0.294 |
| Display area (mm) | 337.92H x 270.33V | 376.32H x 270.33V |
| Surface treatment | Haze 25%, Hard-coating | |
| Surface hardness | 3H | |
| Backlight type | LED | |
| MTBF (hrs) | 30,000 | |

| Audio Option | | |
|--------------|--------------------------|-------------------|
| Input | Connector | 3.5mm stereo jack |
| | Impedance / Power level | 30kΩ / 750mV |
| Output | Connector | 3.5mm stereo jack |
| | Resistance / Power level | 30kΩ / 2.8V |
| Speaker | Dual stereo | 2W x 2 |

| Power | | |
|-----------------------------|---------------------------------------|---------------------|
| Input | Auto-sensing 100 to 240VAC, 50 / 60Hz | |
| Consumption (console / KVM) | Screen on | Max. 25W / Max. 55W |
| | Power saving mode | Max. 4W / Max. 34W |
| | Power button on | Max. 1W / Nil |

| Physical | | RM-113-17 | RM-113-19 |
|-----------------------|------------------|----------------------------------------------|----------------------------------------------|
| Product (W x D x H) | Single console | 442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch | 442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch |
| | Console w/ KVM | 442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch | 442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch |
| Packing (W x D x H) | Single console / | 595 x 860 x 140 mm | 595 x 860 x 140 mm |
| | Console w/ KVM | 23.4 x 33.9 x 5.5 inch | 23.4 x 33.9 x 5.5 inch |
| Net weight | Single console | 12.6 kg / 27.7 lb | 13.2 kg / 29 lb |
| | Console w/ KVM | 13.6 kg / 29.9 lb | 14.2 kg / 31.2 lb |
| Gross weight | Single console | 18.4 kg / 40.5 lb | 19 kg / 41.8 lb |
| | Console w/ KVM | 19.8 kg / 43.6 lb | 20.4 kg / 44.9 lb |

| Environment | |
|------------------------|------------------------------------|
| Operating temp. | 0 to 55°C degree |
| Storage temp. | -20 to 60°C degree |
| Operating humidity | 20~90%, non-condensing |
| Storage humidity | 5 ~90%, non-condensing |
| Operating altitude | 16,000 ft |
| Non-operating altitude | 40,000 ft |
| Shock | 10G acceleration (11ms duration) |
| Vibration | 10~300Hz 0.5G RMS random vibration |

| Mounting Distance | RM-113-17 | RM-113-19 |
|-----------------------------------------------|--------------------------------|--------------------------------|
| Single console drawer / Console w/ KVM drawer | 660 ~ 870 mm 26 ~ 34.3 inch | 660 ~ 870 mm 26 ~ 34.3 inch |

| Compliance | |
|-------------|------------------------------|
| EMC | FCC & CE certified |
| Safety | c UL us & CE / LVD certified |
| Environment | RoHS2 & REACH compliant |