

Benefits

- ▶ 1U 17" / 19" LCD console drawer
- ▶ 1280 x 1024 native resolution / 16.7M colors
- ▶ 104-key keyboard with a true optical mouse
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front handle and two point lock
- ▶ 2-year standard warranty (upgradable up to 5 years)

Options

- DVI-D / HDMI 1.2 video input
- S-Video + Composite (BNC)
- Audio input & output
- DC power : 12V / 24V / 48V / 125V



Product Specifications

Console Port	
Video input	VGA
KB / MS	Combo (USB or PS2)
VGA console 6ft cable : CB-6	Drawer end : DB-15 (VGA + USB KB / MS) Server end : VGA + USB type A

Video Option		
Digital	DVI	DVI-D single link
	HDMI	HDMI 1.2 / HDCP 1.1
Analog	S-Video (4-pin)	NTSC & PAL
	Composite (BNC)	NTSC & PAL

LCD Panel	RA 17"	FA 19"
Panel size (diagonal)	17"	19"
Native resolution	1280 x 1024	1280 x 1024
Brightness (cd/m ²)	250	250
Contrast ratio (typ.)	1000 : 1	1000 : 1
Colors	16.7 M	16.7 M
Viewing angle (L/R/U/D)	85/85/80/80	85/85/80/80
Response time (ms)	5	5
Dot pitch (mm)	0.264	0.294
Display area (mm)	337.92H x 270.33V	376.32H x 270.33V
Surface treatment	Haze 25%, Hard-coating	
Surface hardness	3H	
Backlight type	LED	
MTBF (hrs)	30,000	

Audio Option		
Input	Connector	3.5mm stereo jack
	Impedance / Power level	30kΩ / 750mV
Output	Connector	3.5mm stereo jack
	Resistance / Power level	30kΩ / 2.8V
Speaker	Dual stereo	2W x 2

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 25W / Max. 55W
	Power saving mode	Max. 4W / Max. 34W
	Power button on	Max. 1W / Nil

Physical		RA 17"	FA 19"
Product (W x D x H)	Single console	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch	442 x 700 x 44 mm 17.4 x 27.6 x 1.73 inch
	Console w/ KVM	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch	442 x 700 x 44 mm 17.4 x 27.6 x 1.73 inch
Packing (W x D x H)	Single console /	595 x 860 x 140 mm	595 x 910 x 140 mm
	Console w/ KVM	23.4 x 33.9 x 5.5 inch	23.4 x 35.8 x 5.5 inch
Net weight	Single console	14.3 kg / 31.5 lb	15.3 kg / 33.7 lb
	Console w/ KVM	19.1 kg / 42 lb	20.1 kg / 44.2 lb
Gross weight	Single console	15.3 kg / 33.7 lb	16.3 kg / 35.9 lb
	Console w/ KVM	21.1 kg / 46.4 lb	22.1 kg / 48.6 lb

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20-90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Mounting Distance	RA 17"	FA 19"
Single console drawer / Console w/ KVM drawer	660 ~ 870 mm 26 ~ 34.3 inch	710 ~ 920 mm 28 ~ 36.2 inch

Compliance	
EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS2 & REACH compliant