

## Part# LCD-AP-K17A

### Features

- 6mm aluminum front bezel with hardness glass protect screen
- 17.3 inch TFT LCD wide screen support 4K resolution 3840 x 2160
- Support 1920 x 1080 & 1920 x 1200 resolution
- Display-Port 1.4 x1 , HDMI 2.0 x 2
- Front bezel NEMA4 / IP65 compliant
- Front OSD control buttons to optimize display
- Built in 2x 2watts stereo speakers
- Panel (Flush) mount with clips & Rack Mount ( 7U )
- Meet standard VESA hole, support desk stand / wall mount / Swing Arm mounting

### Option

- DC 9~36 V power input
- AR Hardness glass
- Touch screen



#### LCD Characteristics :

Screen Size	17.3"
Backlight Type	LED
Resolution	3840x2160
Contrast Ratio	1000:1
Brightness ( cd/m2 )	400
View Angles ( H/V )	178/178
Pixel Size ( HxV ) mm	0.0995x0.0995
Max. Color	16.7M
MTBF ( Hrs. )	15,000

#### Input Signals:

Display-Port	Display- Port 1.4 ( 4K-60Hz )
HDMI	2 x HDMI 2.0 ( 4K-60Hz)
Power Input	12V DC jack with hanger
Touch-USB ( option )	USB A Type connector
Touch-RS232 ( option )	D-SUB 9P connector ( Female )

#### User Controls Interface:

Power ON / OFF via Front Button
Power Mode Status LED indicator
OSD ( On Screen Display ) Buttons



#### Power Specifications :

AC Power Input	External Power Adapter , 100-240V AC Input
Wide Range DC Power Input ( option )	Screw Type Terminal Block with internal wide Range DC 9-36V power module

#### Mechanical and Environment:

IP Protect	Front IP65 Grade
Mounting	Rack Mount / Panel ( Flush ) Mount with clips / VESA Mount
Construction	Aluminum Front Bezel + Metal Housing
Operating Temperature	0 - 50 deg. C
Operating Humidity	5% - 95% ( non -condensing )
Anti-Vibration	5 - 500 Hz / 1 Grms PTP
Anti-Shock	15G / Peak ( 11 ms )
Physical Dimension ( WxHxD )	482 x 310(7U) x 47.8 ( mm )
Packing Dimension ( WxHxD )	550 x 420 x 200 ( mm )
Net Weight / Gross Weight	8 / 10.5( KGs )
Certification and Approvals	CE / FCC / RoHS

