



Part# RMD-184

- 1U keyboard drawer
- 104-key keyboard with either touchpad or trackball
- Short depth design of 400mm

Environment Operating temp

Storage temp.

Operating humidity

Storage humidity

Operating altitude

Shock

Vibration

Environment

Non-operating altitude

- Enhanced aesthetics with molded front panel and two point lock
- 2-year standard warranty (upgradable up to 5 years)

Options

MAC or SUN Micro keyboard options available

Product Specifications

Console Port	
KB / MS	USB interface
	Drawer end : attached 6ft USB cable x 2
	Server end: USB type A x 2

Physical		
Dimensions	Product	442 x 400 x 44 mm
(WxDxH)		17.4 x 15.7 x 1.73 inch
	Packing	582 x 500 x 100 mm
		22.9 x 19.7 x 3.9 inch
Weight	Net	8.6 kg / 18.9 lb
	Gross	10.1 kg / 22.2 lb

^{*} All dimensions stated are subject to change if options are selected / integrated to base model part codes

Mounting Distance	
Keyboard drawer	410 ~ 640 mm
	16.1 ~ 25.2 inch

Compliance EMC FCC & CE certified Safety CE / LVD certified

RoHS3 & REACH compliant

-20 to 65°C degree

-20 to 60°C degree

16,000 ft

40,000 ft


20~90%, non-condensing


5 ~90%, non-condensing

10G acceleration (11ms duration)

10~300Hz 0.5G RMS random vibration

Diagrams (mm)








Standard Keyboard













Keyboard Options

Mb Mac keyboard with trackball

* US layout only



Me Mac keyboard with touchpad





Se S keyboard with touchpad



Sb S keyboard with trackball

